

PRODUCT SPECIFICATIONS FOR 313



ENGINE

Net Power - ISO 9249	108 HP
Engine Model	Cat C3.6
Engine Power - ISO 14396	110 HP
Bore	4 in
Stroke	5 in
Displacement	220 in ³

HYDRAULIC SYSTEM

Main System - Maximum Flow	247 L/min (65 gal/min)
Maximum Pressure - Equipment	5075 psi
Maximum Pressure - Travel	5075 psi
Maximum Pressure - Swing	3770 psi

SWING MECHANISM

Swing Speed	11.5 r/min
Maximum Swing Torque	25741 ft·lbf

WEIGHTS

Operating Weight	30400 lb
------------------	----------

SERVICE REFILL CAPACITIES

Fuel Tank Capacity	68.2 gal (US)
Cooling System	4 gal (US)
Engine Oil	2.1 gal (US)
Final Drive - Each	0.8 gal (US)
Hydraulic System - Including Tank	22.5 gal (US)
Hydraulic Tank	18.5 gal (US)
DEF Tank	5.6 gal (US)

DIMENSIONS

Boom	Reach 4.65 m (15'3")
Stick	Reach R3 m (9'8")
Bucket	GD 0.53 m ³ (0.69 yd ³)
Shipping Height - Top of Cab	9.2 ft
Handrail Height	9.2 ft
Shipping Length	25.5 ft
Shipping Length - with Blade	26.4 ft
Tail Swing Radius	7.2 ft
Counterweight Clearance	3 ft
Ground Clearance	1.5 ft
Track Length	12.3 ft

Length to Center of Rollers	9.9 ft
Track Gauge	6.5 ft
Transport Width	8.1 ft

WORKING RANGES & FORCES

Maximum Digging Depth	19.8 ft
Boom	Reach 4.65 m (15'3")
Stick	Reach R3 m (9'8")
Bucket	GD 0.53 m³ (0.69 yd³)
Maximum Reach at Ground Level	29.4 ft
Maximum Cutting Height	28.9 ft
Maximum Loading Height	21 ft
Minimum Loading Height	5.2 ft
Maximum Depth Cut for 2440 mm (8 ft) Level Bottom	19.2 ft
Maximum Vertical Wall Digging Depth	17 ft
Minimum Working Equipment Radius	8.4 ft
Bucket Digging Force - ISO	22180 lbf
Stick Digging Force - ISO	13330 lbf

AIR CONDITIONING SYSTEM

Air Conditioning	The air conditioning system on this machine contains the fluorinated greenhouse gas refrigerant R134a (Global Warming Potential = 1430). The system contains 0.85 hg of refrigerant which has a CO2 equivalent of 1.216 metric tonnes.
------------------	--

SUSTAINABILITY

Recyclability

95%

313 STANDARD EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

CAB

Rollover protective structure (ROPS)

CAT TECHNOLOGIES

Cat Product Link

Remote Flash

Remote Troubleshoot

Cat Grade with 2D

Cat Assist

Cat Payload

2D E-Fence

ELECTRICAL SYSTEM

Maintenance free battery

LED chassis light, left-side/right-side boom lights, cab lights

Centralized electrical disconnect switch

Programmable time-delay LED working lights

ENGINE

Cat C3.6 single turbo diesel engine

One-touch low idle with auto engine speed control

Auto engine shutdown

52°C (125°F) high-ambient cooling capacity without de-rate

-25°C (-13°F) cold start capability

Electric fuel priming pump

Variable speed fan

Single fuel filtration system

Double element air filter with integrated precleaner

Biodiesel capability up to B20

HYDRAULIC SYSTEM

Boom and stick regeneration circuit
Auto hydraulic warm up
Auto two speed travel
Electric main control valve
Boom and stick drift reduction valve
Swing drive with fine swing control function
Auxiliary line support

SAFETY AND SECURITY

Rear and right-side-view cameras
Hydraulic lock out lever
Ground-level engine shutoff switch
Service platform with anti-skid plate and countersunk bolts
Signaling/warning horn

SERVICE AND MAINTENANCE

Grouped engine oil and fuel filters
Ground-level engine oil dipstick
Sampling ports for Scheduled Oil Sampling (S·O·S)

UNDERCARRIAGE AND STRUCTURES

Long undercarriage
Grease lubricated track link
Tie down points on base frame
2470 kg (5,445 lb) counterweight

313 OPTIONAL EQUIPMENT

NOTE

Standard and optional equipment may vary. Consult your Cat dealer for details.

BOOM AND STICKS

4.65 m (15'3") Reach boom
2.4 m (7'8") stub + 2.44 (8'0") fore Variable Angle boom
2.2 m (7'3") Reach stick
2.5 m (8'2") Reach stick
2.8 m (9'2") Reach stick
3.0 m (9'10") Reach stick
2.8 m (9'2") Thumb Ready stick

CAB

Deluxe Cab: air suspension heated seat, 10" touch screen monitor
Premium Cab: air suspension heated and cooled seat, 10" touch screen monitor
Cat Stick Steer
Auxiliary relay

CAT TECHNOLOGIES

Cat Grade with Advanced 2D
Cat Grade with 3D single GNSS
Cat Grade with 3D dual GNSS

ELECTRICAL SYSTEM

360° lighting

HYDRAULIC SYSTEM

Boom and stick lowering check valves
Medium-pressure line
High-pressure line
Quick coupler line

SAFETY AND SECURITY

Cat Detect - People Detection
Cat Command remote control
360° visibility
Swing alarm
Inspection lighting

SERVICE AND MAINTENANCE

Integrated vehicle health management system

UNDERCARRIAGE AND STRUCTURES

500 mm (20") triple grouser shoes
500 mm (20") rubber track shoes
500 mm (20") triple grouser shoes with rubber pad
600 mm (24") triple grouser shoes
600 mm (24") rubber track shoes
700 mm (28") triple grouser shoes
770 mm (30") triple grouser shoes
2500 mm (8'2") blade
2600 mm (8'6") blade
2700 mm (8'10") blade